

Pipe Clamp Sensor

Sensor: Pt100 Pt1000
 according to DIN EN 60751 others _____

Tolerance: class B class 1/3 B
 class 1/10 B class A

Circuits: 2-wire 3-wire
 4-wire

Probe Diameter: 3.0 mm 6.0 mm 8.0 mm
 others _____

Construction: stainless steel sensor sleeve (mat.-no.: 1.4571);
 Ø like probe diameter
 others _____

Probe Length "A": please specify _____ mm

Pipe Clamp: stainless st.; 11.0 mm wide, span diam.: 15.0 - 35.0 mm
 stainless st.; 12.0 mm wide, span diam.: 50.0 - 70.0 mm
 stainless st.; 12.0 mm wide, span diam.: 90.0 - 110.0 mm
 others _____

Lead Wire: flexible lead wire, insulated with
 silicone (-50 °C - 180 °C)
 fiberglass (400 °C, for a short time to 500 °C)
 PVC (-25 °C - 105 °C, for a short time to 125 °C)
 others _____

Further possibilities and information on our cable and wire range can be found on page 122.

Wire Length "B": please specify _____ mm

Termination: plug jack
 Lemo: please specify size _____
 Tuchel: please specify size _____
 Binder: please specify size _____
 Fischer: please specify size _____
 bare ends
 others _____

Further information on our connector range can be found on page 94.

Quantity: _____ piece(s)

